



Product Data Sheet

API CF-4 20W-40 Diesel Engine Oil

AMARON HI-LIFE LUBES API CF-4 20W-40 is top tier multi-grade diesel engine crankcase oil manufactured from premium quality virgin base stock. It is fortified with a shear stable viscosity index improver and high-performance engine oil additives. It also contains a special additive to retard soot induced oil thickening, particularly for engines emitting black exhaust smoke. As a result, oil in service does not thicken much, while the engine runs over a longer period

Applications:

AMARON HI-LIFE LUBES API CF-4 20W-40 40 is recommended as extended drain service engine oil for new generation diesel engines meeting Bharat I/Euro I emission norms, manufactured by caterpillar, Cummins, Tata Motors, Ashok Leyland, Swaraj Mazda, Eicher, Ford, Toyota, Simpson etc.

Advantages:

- Extends engine life
- Resists oil thickening
- Reduces fuel consumption
- Reduces maintenance cost
- Protects from rust and corrosion
- Prevents carbon built-up in engines

Performance Level:

- API CF-4

Technical values:

Appearance	Clear and Bright
Kinematic Viscosity@100°C, mm ² /sec	14
Viscosity Index	110
Flash Point, COC, °C	200
TBN, mg KOH/gm	6.0
Pour Point, °C	(-)24

In pursuit of continuous improvement, these figures may be changed without notice at the sole discretion of Amaron High Life Lubes. All recommendation and suggestions are without guarantee as condition of use are beyond AREML controls.